




$$L1 = 2.54 * (\text{No. of pin} / 2)$$

$$L2 = 2.54 * (\text{No. of pin} / 2 - 1)$$



RECOMMENDED P.C.B. LAYOUT

specifications

current rating:3amp
voltage rating:250V ac max
insulator resistance:5000 M ohms min.
contact resistance:20 m ohms max.
dielectric withstanding:500v ac for one minute
operating temperature:-40°C--+105°C(ny6t/ny9t)
max.processing temp:245±5°C for 3-5seconds(ny6t/ny9t)

contact material:phosphor bronze
insulator material:nylon6t nylon9t
color:black
finish:gold flash

packing:tube

HOW TO ORDER

HT254F50-X-1/2*X-X

Base No

V6:6T
V9:9T

Single row/Dual rows

number of circuit
02-40

type no.

HTE TECHNOLOGY CO.,LTD
HTE 興田科技有限公司

CUSTOMER APPROVAL

P/N

HT254F50X-2*X-508

UNIT

mm

SIZE

A4

TITLE

2.54mm Female Header dual rows
dual entry type508

GENERAL
TOLERANCE
0.=±0.30
0.0=±0.20
0.00=±0.15

SCALE

3:1

SHEET

1/1

REV.

DESCRIPTION

DATE

DRAWN

LILY

CHECKED

SANDY